



SPECIAL LITE

QUALITY OUTDOOR PRODUCTS SINCE 1967

1634 Latrobe Derry Road
Loyalhanna, PA 15661
Toll Free: 1-800-365-0511
Phone: (724) 537-4711
www.specialliteproducts.com
customer_service@specialliteproducts.com

MODEL NUMBER: BL-104


11" W x 4 3/4" Dia. x 42" H LED Aero Bollard

How to Order:

Follow the below guide and table for item numbers.

1 BL-104- BLK / AB
QTY Item # Finish

OPTIC:	Wide Beam Spread
WATTAGE:	25w
VOLTAGE:	120-277V
KELVIN:	4000K
LENS:	Soft LED LumaLens Opal
FINISH:	BLK = Black, AB = Architectural Bronze



Dimensions

Width (B)	11" (280mm)
Diameter (D)	4 3/4" (120mm)
Height (A)	42" (1,067mm)

EasyLED Technology

The BL-104 with UV-Stabilized Polycarbonate lenses and sealed optical compartments are designed to replace HID lighting systems up to 70w MH or HPS. These fixtures are ideal for retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities.

Specifications and Features:

Housing:

Extruded Aluminum Housing with Flush Mounting Base, Sand Cast Twin Arm Head, Sealed Driver Compartment.

Listing & Ratings:

ETL: Listed for Wet Locations, ANSI/UL 1598, 8750
IP66 Sealed LED Compartment.

Finish:

Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating.

Lens:

SoftLED LumaLens Opal UV-Stabilized Polycarbonate Vandal-Resistant Inner Lens to Seal LED Array.

Mounting Options:

Mounting Kit with 8" Anchor Bolts, Included.

EasyLED LED:

Aluminum Boards

Wattage:

25w: Array 24.8w, System: 27.1w; (70w HID Equivalent)

Driver:

Electronic Driver, 120-277V, 50/60Hz; Less Than 20% THD and PF>0.90. Standard Internal Surge Protection 2kV. 0-10V Dimming Standard for a Dimming Range of 100% to 10%; Dimming Source Current is 150 Microamps.

Controls:

Fixtures are NOT Designed for Use with Line Voltage Dimmers.

Warranty:

5-Year Warranty for -40°C to +50°C Environment.